




FIBREGRID

SlipGrip® Anti Slip Tape



Product Description

Our SlipGrip® Anti Slip tape is made from aluminium oxide grit, which makes them long-lasting and anti-slip.

They can be used for highlighting hazards and dangers or to indicate a course of action, such as where an escape route is. They come in two different colours; black, yellow.

Use internally or externally (if you are using them outside you'll need our SlipGrip® Tape Primer too).



Product Characteristics

- Easy application with self-adhesive backing
- Long lasting due to a strong resin bonded aluminium oxide anti slip grit
- Water resistant and pressure sensitive
- Disability Discrimination Act (DDA) and 2004 Building Regulations approved



Suitable Applications

Walkways, ramps and stairs.



Suitable Substrates

Wood, concrete, stone and metal.

SlipGrip Anti Slip Tape



Preparation

Ensure the surface is clean, dry, and free from wax, oil, food residue or any other substance likely to affect the application of the tape. Grease and oil should be removed with our SlipGrip Standard Degreaser.

For best results, use our SlipGrip Anti Slip Tape Primer for extra adhesion.



Application

If you are using on steps and nosings leave a gap of about 10mm from the step edge to avoid the tape getting scuffed and thus reducing its life and efficiency. Peel off the backing strip to a length of approximately 50mm, which gives you more control than if you peel off too much. Then, firm the product into place with a hand or foot.

If you are fitting our conformable safety tapes, you may want to use a rubber mallet or similar to ensure the tapes conform the surface and take on its shape.

Do take care not to stretch the tape and only use at temperatures about 10°C.

If you find you've made a mistake, don't worry as the products can be peeled off easily immediately after fitting, but do this straight away.

If you are fitting on surfaces that could get wet, or are likely to experience heavy traffic, the new recommend you use our Anti Slip Tape Edge Sealer.

Anti Slip Tape should be fitted as per the instructions provided.

Anti Slip Tape Primer

This is ideal for porous or dusty surfaces. Simply stir and brush on. Coverage is 2-3m² per 500ml. The appearance when applied is milky, but it dries (in about one hour at 10-15°C) clear.

Make sure you only apply the primer to areas that the products will cover, otherwise dust could settle on exposed primer.

After application, brushes can be washed out in water.

Anti Slip Tape Sealer

If you are using the products where moisture could penetrate the tape edge, or in very heavily-trafficked areas, then we recommend you apply our Anti Slip Tape Sealer. All you need to do is squeeze the sealer from the tube around the tape edge. This will give extra protection and increase the tape's life.



Maintenance

Downtime

Although these products can be walked on immediately, full adhesion takes 24 hours, so be gentle with them during this period and avoid heavy use.

Storage

Keep the product warm and dry before using.

Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP

Online: www.fibregrid.com

Email: sales@fibregrid.com

Phone: 01440 712722

Fax: 01440 712733

